



SERVER

©2010 BitTorrent, Inc.

Table of Contents

Changes

Here are changes and known issues made to μ Torrent Server. Changes are in most-recent-first order.

Changes made that apply to multiple μ Torrent products are summarized in the file `Changes.txt`.

Current Revision

Changes

- Eliminated race condition causing crashes when adding torrents
- Resolved problems associated with moving completed data files

Known Issues

- Guest mode support is broken in the web UI and/or the server
- BEP22 isn't supported on POSIX platforms
- There's no table of contents in the PDF form of the user manual
- Checking for and reporting that product updates are available isn't supported yet
- The web UI doesn't show an indication when a setting change fails to apply because the proposed value was invalid
- The web UI doesn't show an indicator if the port is blocked by a firewall

- The web UI doesn't provide control of RSS actions supported by the server
- The web UI doesn't show status and error messages generated by the server

20110228 - Revision 24733

Changes

- Incorporated bug fixes from generic code
- The `usage` argument now also reports product version information
- Added `Changes.txt` to the archive distributed for this product, so that users would have a list of changes made to parts of code shared with other products
- Stopped requiring that `/etc/fstab` not be empty, so that program will run on certain VMs

20110118 - Revision 24118

Changes

- Incorporated bug fixes from generic code
- Added SSL support, requiring load-time resolution of `libssl` and `libcrypto`

20101206 - Revision 23418

Changes

- Fixed bug in web UI causing failure to run on Internet Explorer

20101111 - Revision 23090**Changes**

- Enhanced speculative fix for crash on POSIX platforms occurring when any configurable directories (e.g., active, completed, temporary, autoload, request) contain other than 7-bit characters, which should improve the experience of users using Cyrillic characters (the behavior in that case worsened after the previous release because the previous fix was incomplete)
- Fixed crash when choosing to use an active directory without supplying a path to that directory (seen when users attempt to specify a nonexistent directory (possibly by misspelling the desired existing directory) for the active directory via the web UI)

20101027 - Revision 22789**Changes**

- Added fields to the About box in the web UI to present the external IP address and UDP/TCP ports assigned by a UPnP router to the server
- Added speculative fix for crash on POSIX platforms occurring when any configurable directories (e.g., active, completed, temporary, autoload, request) contain Unicode characters
- Fixed documentation by changing `feed_id` to `feed-id` in two places

20101022 - Revision 22708**Changes**

- Added `daemon` argument which directs the server to run in its own process group
- Added `usage` argument which directs the server to display the set of valid command-line arguments before exiting - server also prints error and usage messages before exiting if it detects at least one unrecognized command-line argument
- Added settings `finish_cmd` and `state_cmd` to provide a way to invoke asynchronous processes for torrent lifecycle events
- The add torrent dialog in the web UI now allows the user to choose which download directory to use for the torrent being added
- Correct JSON output is now generated for the `list-dirs` action request
- The name of the directory created by extracting the product archive now includes `utorrent` instead of `bittorrent`
- Removed `ul_slots_per_torrent` setting since it no longer has a function
- Added `ut_webui_dir` setting in the configuration file, which specifies the directory containing the `webui.zip` archive or the unarchived files to be served for the web UI
- Added `pidfile` argument which permits the specification of a file to be created by the `utserver` process which will contain the ID of the `utserver` process
- Added `logmask` setting in the configuration file which permits logging to be configured (and subsequently modified as part of handling a hangup signal), and removed support for `LOGMASK` environment variable
- The server rereads the configuration file upon receipt of a hangup signal or when creating or moving a file named `rcf.utmr` in the `dir_request` directory - see the cautions in the user manual about sending a hangup signal when attempting to change the value of `dir_request`

- Added settings `admin_name` and `admin_password` to allow administrators to define initial non-default credentials for authenticating to the server via the HTTP interface
- Fixed documentation by changing `filter_id` to `filter-id` in one place

20100913 - Revision 21886

Changes

- Ensure alternative listening port setting persists when changed via web UI
- Include changes list in `docs` directory of product archive
- Add mention of `configfile` and `settingspath` command-line arguments, rearrange content of **Getting Started** section of user manual
- Support `configfile` argument to specify configuration file location
- Disable BEP22 DNS support on POSIX platforms
- Include plain text version of the user manual in `docs` directory of product archive
- Include a EULA file in the `docs` directory of the archive
- Change default log file for `logfile` argument to `utserver.log`
- Fix documentation error saying to use forward slash (/) to precede a command-line argument keyword - should use a dash (-) on POSIX systems

20100902 - Revision 21701

First release.